

# 1812 CLASSIC IELEPHONE INTERCOM SYSTEM





surface mount

- Unique communication and access control system allows homeowners to use their telephone as an intercom to speak to a guest at a front door or gate
- System connects directly to the homeowners existing telephone line.
   No additional monthly expenses for a separate telephone line
- Calls from access system are identified with a double ring. Homeowners know instantly if a call is coming from their door or gate
- Built-in call waiting assures that incoming or guest calls are not missed
- 2 year limited factory warranty



wall mount

**grant guest access** by pressing 9 on the telephone



Hi quality communication – the same standard that the phone company uses



\*JKS

modular design
makes installation and service easy



**talk** to front door or gate from any telephone in the home

## INTERCOM SYSTEM











1812 Surface

10" W x 6.13" H x 5.25" D (254mm W x 156mm H x 133mm)

1812 Flush

11.88" W x 9.13" H x 4.5" D (302mm W x 232mm H x 114mm D)

1812 Wall

10.75" W x 7.38" H x 3.5" D (273mm W x 187mm H x 88.9mm D)

1812	PHONE # MEMORY	ENTRY CODES	DEVICE CODES	RELAYS	DIRECTORY	ELEVATOR CONTROL	PROGRAMMING OPTIONS	OPTIONS	TRANSACTION BUFFER
Surface Mount	3	50 (4-digit)	N/A	2	-	-	Keypad Touch-Tone Phone	Gold Plated Faceplate	-
Flush Mount	3	50 (4-digit)	N/A	2	-	-	Keypad Touch-Tone Phone	Gold Plated Faceplate	-
Wall Mount	3	50 (4-digit)	N/A	2	-	-	Keypad Touch-Tone Phone		-

## **Technical Features**

### Mechanical

Stainless steel faceplate

Galvanized steel sub-plate

Metal keypad

Offset speaker holes for protection

Indoor or outdoor applications

Enclosures are NEMA 4x rated

Hands free

### **Electrical**

24 VAC (power transformer included)

Full Duplex voice communication

Unique ring

Call waiting

Call forwarding

Three (3) preprogrammed call out phone numbers

Special intercom mode for use with KSU and PBX phone systems

Four-digit entry codes (50)

Built-in time clock

Entry code time zones

Call forwarding time zone

Hold open time zones (4)

Do not disturb time zone

Flash entry codes

Two relays to control two entry points

Multiple systems may share same phone line

Secondary keypad can be added for entry code access at a second door or gate

### **Miscellaneous**

Environmental: 10°F to 145°F (-12°C to 62°C)

Camera Ready: Optional CCTV camera\* \*may require additional CCTV equipment

Shipping weight approximately 15 Lbs (7 kg)



FCC (US) DUF6VT-12874-0T-0 DOC (CAN) 1736 4507 A

Distributed by:



Power Door Products

(914) 698-5083

www. Power Door Products. com

**MEMBER:** 













DOORKING, INC.